

SPECIFICATIONS

Output Frequency

Tuning range:	6780 - 7880 MHz
Frequency step size:	100 kHz
Frequency stability and accuracy (Ext ref):	Same as input
Frequency stability and accuracy (Int ref):	±1 PPM (over temp range)
Aging (After 2 months):	±1 PPM max per year @ 25°C
Adjustability (typ.):	10 years
Phase noise in dBc/Hz (typ.):	L(100 Hz) -80
	L(1 kHz) -85
	L(10 kHz) -85
	L(100 kHz) -95
	L(1 MHz) -120
Spurious:	-60 dBc
Harmonics (typ.):	-20 dBc
Power out (min.):	13 dBm
Output power variation (freq. & temp.):	3 dB
Load VSWR:	2:1

Input Frequency

Input reference frequency:	5 MHz, 10 MHz or Internal
Input ref. freq. level:	0 dBm ±3dB

Frequency Tuning / Alarm

Frequency control:	Serial RS-232 / RS-422 / RS-485
Acquisition time:	100 msec
Phase-lock indicator:	High = lock (Open collector or CMOS / TTL)

DC Power


+5.2VDC (min) +7.0VDC (max)	750 mA
+15.0VDC (min) +17.0VDC (max)	150 mA

Mechanical

RF connectors:	2 SMA (F)
Digital & DC connection:	DB15 (M)

Environment

Operating temperature range (surface):	-10°C to 70°C
Storage temperature range:	-40°C to 85°C
Relative humidity (non-condensing):	90%RH @ 40°
Shock:	30 G / 10msec
Vibration:	4 G / 20 Hz - 20 kHz
EMI leakage(typ):	-85 dBc



Notes:

1. This is an EMI gasketed package with a filtered DB15 connector.
2. Use Rev. E (09-06-05) of the Interface Definition for this unit.

luff RESEARCH, inc.		
FLORAL PARK, NY		
PHONE: (516) 358-2880 FAX: (516) 358-2757		
PRODUCT DATA SHEET		
TLSD FREQUENCY SYNTHESIZER		
Model: TLSD67807880/100K	Rev. B	09/15/05